AAD-OUT4-F32

4-Channel Analog & Digital Audio Output Card

AAD-OUT4-F32 is a four-channel analog and digital output card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The AAD-OUT4-F32 outputs four analog and digital signals from the chassis

FEATURES

Balanced Analog Audio over Terminal Block Connector
S/PDIF Digital Audio over RCA Connector

KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	4 S/PDIF (digital audio) on RCA connectors, 4 balanced audio stereo (analog audio) on 5−pin terminal blocks
TOTAL BANDWIDTH:	Analog (−3db): >100kHz, Digital: 32kHz − 192kHz sample frequency
POWER CONSUMPTION:	10W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	−40° to +70°C (−40° to 158°F)
HUMIDITY:	10% to 90%, RHL non−condensing
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
PRODUCT DIMENSION:	22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H
PRODUCT WEIGHT:	0.3kg (0.7lbs) approx
SHIPPING DIMENSION:	25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx